



FEATURES AND BENEFITS

- Lead-free, copper-free, corrosion-resistant DuraMirror™ glass
- Wall-glow ambient lighting on all four sides with diffuser for a finished side view
- Forward-phase dimming technology
- Suitable for damp bathroom environments
- Environmentally sustainable
- Energy efficient
- Fast lead times
- Easy installation
- ADA compliant
- Title 24 compliance available
- 7-year limited warranty
- Covered by one or more patents
- Made in America with U.S. and global components

AVAILABLE OPTIONS

- Custom sizes

LIGHTING SPECIFICATIONS

- Natural-looking LED light color
- CRI: 90+
- CCT: 3,000 Kelvin
- Replaceable LEDs
- 695 lumens per foot
- Maximum 100 lumens per watt efficacy
- Calculated L70 52,000-hour LED lifespan

SAFETY SPECIFICATIONS

- Entire assembly meets UL/cUL standards
- International certifications
- Safety-backed mirror

PRODUCT DESCRIPTION

Within an atmosphere of peaceful bliss and ethereal light, you'll find Serenity™. Loved for its perpetually elegant design and beautiful ambient wall glow, this splendid centerpiece can transform any room into a calming oasis.

SPECIFICATION STATEMENT

Solution shall consist of a mirror with wall-glow accent light around the mirror which provides uniform light to the walls at all edges of the mirror. It shall have corrosion-resistant glass. The mirror shall use replaceable LEDs with greater than or equal to 90 CRI (color rendering index). Product will be made in America with U.S and global components and have a 7-year limited warranty.

THE ELECTRIC MIRROR ADVANTAGE

- ☑ Global mirror technology leader for over 20 years
- ☑ More installations than all competitors combined
- ☑ Realistic warranty you can believe in and trust
- ☑ Lowest total cost of ownership
- ☑ U.S. based customer service support
- ☑ 125,000 square foot American manufacturing facility

INSTALLATION SPECIFICATIONS

- 120V-240V hardwire electrical connection; provide 36" whip; junction box not required
- Chassis should be mounted to wall studs; mounting holes are provided
- Controlled by forward-phase dimming wall switch
- Fixture can only be hung in the WxH orientation as shown; fixture is not field-interchangeable

MODELS

Base Model	Dimensions	Power Requirements
SER-2436	24"W x 36"H x 1.75"D (610mm x 914mm x 44mm)	120/240 VAC, 86W
SER-3636	36"W x 36"H x 1.75"D (914mm x 914mm x 44mm)	120/240 VAC, 106W
SER-4836	48"W x 36"H x 1.75"D (1219mm x 914mm x 44mm)	120/240 VAC, 126W
SER-6036	60"W x 36"H x 1.75"D (1524mm x 914mm x 44mm)	120/240 VAC, 146W

*Base model number shown only. To specify additional options, contact Electric Mirror at residential@electricmirror.com.

DIMENSIONAL DRAWING (Not to scale. Frost and border widths may vary depending on mirror size.)

