



PRODUCT DESCRIPTION

The soothing, rounded shape of this elegant lighted mirror evokes a calm and Placid™ response. Featuring impact-resistant polycarbonate, this mirrored centerpiece is ideal for environments where tamper-resistant and impact-resistant mirrors are preferred.

SPECIFICATION STATEMENT

Solution shall consist of a polycarbonate, lighted mirror with forward-facing task lighting. Mirror shall have uniform light output in frosted areas, using LEDs with greater than or equal to 90 CRI (color rendering index). Product will be made in America with U.S. and global components and have a 5-year limited warranty.

THE ELECTRIC MIRROR ADVANTAGE

- ☑ Global mirror technology leader for over 25 years
- ☑ More installations than all competitors combined
- ☑ Realistic warranty you can believe in and trust
- ☑ Lowest total cost of ownership
- ☑ U.S.-based customer service support
- ☑ 125,000 square foot American manufacturing facility

FEATURES AND BENEFITS

- Impact-resistant polycarbonate mirror
- Scratch-resistant coating
- Forward-facing task lighting
- IP65 rated*
- Suitable for damp locations
- IK10 impact rated
- Tamper-resistant hardware
- Energy efficient
- ADA compliant
- Title 24 compliance available
- 5-year limited warranty
- Made in America with U.S. and global components

AVAILABLE OPTIONS

- CCT: 2,700K-6,500K
- 0-10V dimming
- Forward-phase dimming
- Custom sizes ¹
- 277V available ²

LIGHTING SPECIFICATIONS

- Natural-looking LED light color
- CRI: 90+
- CCT: 3,500 Kelvin
- 604 lumens per foot
- Maximum 100 lumens per watt efficacy
- Calculated L₇₀ 124,000-hour LED lifespan

SAFETY SPECIFICATIONS

- Entire assembly meets UL/cUL standards
- Ligature resistant

¹ Minimum order quantity required

² May not be compatible with all upgrades and options

INSTALLATION SPECIFICATIONS

- 120V-240V hardwire electrical connection; provide 36" whip; junction box not required
- Chassis to be recessed in wall and mounted to wall studs; mounting holes are provided
- Installation requires bead of pick-proof silicone (not included) around perimeter of mirror*
- Controlled by on/off wall switch
- Installation wiring may be different on mirrors equipped with additional options
- Fixture can only be hung in the WxH orientation as shown; fixture is not field-interchangeable
- Contact Electric Mirror for unique product installation and rough-in details

*IP65 rating requires bead of pick-proof silicone around perimeter of mirror

MODELS

Base Model**	Dimensions	Power Requirements
PLA-30.00-L7-35K	30" diameter x 2"D (762mm x 51mm)	120/240 VAC, 22W
PLA-36.00-L7-35K	36" diameter x 2"D (914mm x 51mm)	120/240 VAC, 28W
PLA-24.00x36.00-L7-35K	24"W x 36"H x 2"D (610mm x 914mm x 51mm)	120/240 VAC, 28W

**Base model number shown only. To specify additional options, contact Electric Mirror at sales@electricmirror.com

DIMENSIONAL DRAWING *(Not to scale. Frost and border widths may vary depending on mirror size.)*

