



PRODUCT DESCRIPTION

Your corridors will take on the glamour of Fifth Avenue with this stunning and functional lighted mirror sconce. Featuring a smooth polished edge with two vertical frames of light, this luminaire is a certain hospitality fashion trend-setter.

SPECIFICATION STATEMENT

Solution shall consist of a lighted mirror sconce with forward-facing lighting and corrosion-resistant glass. Mirror shall have uniform light output in frosted areas, using replaceable LEDs with greater than or equal to 90 CRI (color rendering index). Product will have a 10-year limited warranty.

FEATURES AND BENEFITS

- Lead-free, copper-free, corrosion-resistant OmegaMirror™
- Forward-facing lighting
- Environmentally sustainable
- Energy efficient
- Fast lead times
- Easy installation
- 10-year limited warranty
- Designed in the USA

AVAILABLE OPTIONS

- Room numbers ¹

LIGHTING SPECIFICATIONS

- Natural-looking LED light color
- CRI: 90+
- CCT: 3,000K
- Replaceable LEDs
- 516 initial lumens/foot
- Maximum 96 lumens/watt efficacy
- Calculated L₇₀ 50,000-hour LED lifespan

SAFETY SPECIFICATIONS

- Entire assembly meets UL/cUL standards
- International certifications
- Safety-backed mirror

¹Minimum order quantity required

THE ELECTRIC MIRROR ADVANTAGE

- ☑ Global mirror technology leader for over 25 years
- ☑ More installations than all competitors combined
- ☑ Realistic warranty you can believe in and trust
- ☑ Lowest total cost of ownership
- ☑ U.S.-based customer service and support
- ☑ 125,000-square-foot American manufacturing facility

Fifth Avenue™ Corridor Lighting

Product Specifications

ELECTRIC MIRROR®

INSTALLATION SPECIFICATIONS

- 120V-240V hardwire electrical connection; provide 12" whip; junction box not required
- Chassis should be mounted to wall studs; mounting holes are provided
- Fixture can only be hung in the WxH orientation as shown; fixture is not field-interchangeable

MODELS

Base Model*	Model Type	Dimensions	Power Requirements
SCO2-FIF-5.00x24.00-LSO-OS-30K	Standard	5" W x 24" H x 1.7" D (127mm W x 610mm H x 43mm D)	120/240 VAC, 9W
SCO2-FIF-5.00x42.00-LSO-OS-30K	Standard	5" W x 42" H x 1.7" D (127mm W x 1,067mm H x 43mm D)	120/240 VAC, 17W

*Base model number shown only. To specify additional options, contact Electric Mirror at sales@electricmirror.com.

DIMENSIONAL DRAWING (Not to scale.)

