




**FEATURES AND BENEFITS**

- Lead-free, copper-free, corrosion-resistant OmegaMirror™
- Inward-facing task lighting for brilliant facial illumination
- Wall-glow ambient lighting with diffuser for a finished side view
- Greater illuminance with half the power consumption of traditional LED mirrors
- 0-10V dimming
- Sleek and modern profile
- Suitable for damp bathroom environments
- Environmentally sustainable
- Energy efficient
- Easy installation
- Title 24 compliant
- JA8-2022 compliant
- 10-year limited warranty
- Patent: [www.electricmirror.com/patents](http://www.electricmirror.com/patents)
- Designed in the USA

**AVAILABLE OPTIONS**

- Round or oval shape

**FINISHES**



- Other finishes available <sup>1</sup>

**LIGHTING SPECIFICATIONS**

- Natural-looking LED light color
- CRI: 90+
- CCT: 3,000K
- 351 initial lumens/foot (front lighting)
- Maximum 98 lumens/watt efficacy
- Reported L<sub>70</sub> >54,000-hour LED lifespan
- Built-in EMX diffusers

<sup>1</sup> Minimum order quantity required

**PRODUCT DESCRIPTION**

Combining a timeless, balanced shape with inward-facing directional lighting is sheer Brilliance™. The front-lit design of this modern, slim-profile mirror elevates task lighting to a level never before seen.

**SPECIFICATION STATEMENT**

Solution shall consist of a round or oval lighted mirror with integrated one-touch dimming and one-touch wall glow. LEDs will be mounted in a 45-degree channel in the frame of the mirror, with inward-facing directional lighting on the front face of the mirror and ambient wall glow behind the mirror. LEDs will be covered by an integrated diffuser and shall have an L<sub>70</sub> life of >54,000 hours, with a greater than or equal to 90 CRI (color rendering index). Product shall incorporate a driver enclosure that is to be mounted to the back of the mirror. Product will have a 10-year limited warranty.

**THE ELECTRIC MIRROR ADVANTAGE**

- ✓ Global mirror technology leader for over 25 years
- ✓ More installations than all competitors combined
- ✓ Realistic warranty you can believe in and trust
- ✓ Lowest total cost of ownership
- ✓ U.S.-based customer service support
- ✓ 125,000-square-foot American manufacturing facility

**SAFETY & INSTALLATION SPECIFICATIONS**

- Entire assembly meets UL/cUL standards
- Safety-backed mirror
- 120V hardwire electrical connection; junction box required
- Fixture should be mounted to wall studs; wall cleat provided
- Controlled by non-dimming wall switch for on/off, or 0-10V dimming wall switch
- Fixture can only be hung in the WxH orientation as shown; fixture is not field-interchangeable

**MODELS**

Base Model*	Finish	Dimensions	Power Requirements
BRI3-24.00X36.00-01L-D1-OS-WG3-30K	Matte Black	24" W x 36" H x 2.10" D (oval) (610mm W x 914mm H x 53mm D)	120V, 72W
BRI3-24.00X36.00-02V-D1-OS-WG3-30K	Brushed Brass		
BRI3-30.00-01L-D1-OS-WG3-30K	Matte Black	30" DIA x 2.10" D (round) (762mm DIA x 53mm D)	120V, 71W
BRI3-30.00-02V-D1-OS-WG3-30K	Brushed Brass		
BRI3-36.00-01L-D1-OS-WG3-30K	Matte Black	36" DIA x 2.10" D (round) (914mm DIA x 53mm D)	120V, 87W
BRI3-36.00-02V-D1-OS-WG3-30K	Brushed Brass		

\*Base model number shown only. To specify additional options, contact Electric Mirror at [sales@electricmirror.com](mailto:sales@electricmirror.com).

**DIMENSIONAL DRAWING** (Not to scale.)

