

Eminence™ Lighted Mirror

Product Specifications: Commercial


ELECTRIC MIRROR®



FEATURES AND BENEFITS

- Lead-free, copper-free, corrosion-resistant OmegaMirror™
- Inward-facing task lighting for brilliant facial illumination
- Wall-glow ambient lighting with diffuser for a finished side view
- Greater illuminance with half the power consumption of traditional LED mirrors
- 0-10V dimming
- Sleek and modern profile
- Suitable for damp bathroom environments
- Environmentally sustainable
- Energy efficient
- Easy installation
- Title 24 compliant
- JA8-2022 compliant
- 10-year limited warranty
- Patent pending
- Designed in the USA

FINISHES



- Other finishes available ¹

LIGHTING SPECIFICATIONS

- Natural-looking LED light color
- CRI: 90+
- CCT: 3,000K
- 351 initial lumens/foot (front lighting)
- Maximum 98 lumens/watt efficacy
- Calculated L₇₀ 54,000-hour LED lifespan
- Built-in EMX diffusers

¹ Minimum order quantity required

PRODUCT DESCRIPTION

This lighted mirror has risen to a place of Eminence™ among designers, bringing prestige and distinction to every room it graces. A unique shadow-box frame, inward-facing task lighting, and ambient wall glow combine to create a perfect balance of form and function.

SPECIFICATION STATEMENT

Solution shall consist of a lighted mirror with integrated one-touch dimming. LEDs will be mounted in a 90-degree channel in the frame of the mirror, with inward-facing directional lighting on the front face of the mirror and ambient glow behind the mirror. LEDs shall have an L₇₀ life of >54,000 hours, with a greater than or equal to 90 CRI (color rendering index) and will be covered by an integrated diffuser. Product shall incorporate a driver enclosure that is to be mounted to the back of the mirror. Product will have a 10-year limited warranty.

THE ELECTRIC MIRROR ADVANTAGE

- ✓ Global mirror technology leader for over 25 years
- ✓ More installations than all competitors combined
- ✓ Realistic warranty you can believe in and trust
- ✓ Lowest total cost of ownership
- ✓ U.S.-based customer service and support
- ✓ 125,000-square-foot American manufacturing facility

Eminence™ Lighted Mirror

Product Specifications: Commercial

ELECTRIC MIRROR®

SAFETY & INSTALLATION SPECIFICATIONS

- Entire assembly meets UL/cUL standards
- Safety-backed mirror
- 120V hardwire electrical connection; 36" whip provided with mirror; junction box controlled by a wall switch (by others) is required
- Fixture should be mounted to wall studs; wall cleat provided
- Controlled by non-dimming wall switch for on/off, or 0-10V dimming wall switch
- Fixture can only be hung in the WxH orientation as shown; fixture is not field-interchangeable

MODELS

Base Model*	Finish	Dimensions	Power Requirements
EMN3.1-24.00X36.00-01L-D1-OS-RC6.0-WG3-30K	Matte Black	24" W x 36" H x 2.17" D	120V, 82W
EMN3.1-24.00X36.00-02V-D1-OS-RC6.0-WG3-30K	Brushed Brass	(610mm W x 914mm H x 55mm D)	
EMN3.1-30.00X42.00-01L-D1-OS-RC6.0-WG3-30K	Matte Black	30" W x 42" H x 2.17" D	120V, 101W
EMN3.1-30.00X42.00-02V-D1-OS-RC6.0-WG3-30K	Brushed Brass	(762mm W x 1,067mm H x 55mm D)	

*Base model number shown only. To specify additional options, contact Electric Mirror at sales@electricmirror.com.

DIMENSIONAL DRAWING (Not to scale.)

