



PRODUCT DESCRIPTION

Bathe in the celestial aura of the Luna™ lighted mirror. The luminous ambient wall glow exudes a sense of grandeur and elegance, transforming your space into a realm of breathtaking beauty.

SPECIFICATION STATEMENT

Solution shall consist of a mirror with wall-glow accent light around the mirror which provides uniform light to the walls at all edges of the mirror. It shall have corrosion-resistant glass. The mirror shall use replaceable LEDs with greater than or equal to 90 CRI (color rendering index). Product will be made in America with U.S and global components and have a 10-year limited warranty.

THE ELECTRIC MIRROR ADVANTAGE

- ✓ Global mirror technology leader for over 25 years
- ✓ More installations than all competitors combined
- ✓ Realistic warranty you can believe in and trust
- ✓ Lowest total cost of ownership
- ✓ U.S.-based customer service support
- ✓ 125,000-square-foot American manufacturing facility

FEATURES AND BENEFITS

- Lead-free, copper-free, corrosion-resistant OmegaMirror™
- Wall-glow ambient lighting with diffuser for a finished side view
- Suitable for damp bathroom environments
- Environmentally sustainable
- Energy efficient
- Fast lead times
- Easy installation
- ADA compliant
- JA8-2022 compliant
- 10-year limited warranty
- Patent: www.electricmirror.com/patents
- Made in America with U.S. and global components

AVAILABLE OPTIONS

- Title 24 compliance ¹
- Keen™ Technology ³
- Clock Technology ³
- Defogger
- 0-10V dimming ²
- Forward-phase/triac dimming ²
- 277V power ²
- Custom sizes

LIGHTING SPECIFICATIONS

- Natural-looking LED light color
- CRI: 90+
- CCT: 3,000K
- Replaceable LEDs
- 823 initial lumens/foot
- Maximum 100 lumens/watt efficacy
- Calculated L₇₀ 52,000-hour LED lifespan

SAFETY SPECIFICATIONS

- Entire assembly meets UL/cUL standards
- International certifications
- Safety-backed mirror

¹ Title 24 compliance requires 0-10V or forward-phase/triac dimming

² Minimum order quantity required

³ See technology specification sheets for more details

Luna™ Lighted Mirror

Product Specifications

ELECTRIC MIRROR®

INSTALLATION SPECIFICATIONS

- 120V-240V hardwire electrical connection; provide whip; junction box not required
- Chassis should be mounted to wall studs; mounting holes are provided
- Controlled by non-dimming on/off wall switch

MODELS

Base Model*	Dimensions	Initial Lumens/Fixture	Power Requirements
LUN2-30.00-L7SHD-NB-30K	30" DIA x 1.75" D (762mm DIA x 44mm D)	5,075	120/240 VAC, 60W
LUN2-36.00-L7SHD-NB-30K	36" DIA x 1.75" D (914mm DIA x 44mm D)	6,309	120/240 VAC, 75W
LUN2-42.00-L7SHD-NB-30K	42" DIA x 1.75" D (1,067mm DIA x 44mm D)	7,544	120/240 VAC, 89W
LUN2-48.00-L7SHD-NB-30K	48" DIA x 1.75" D (1,219mm DIA x 44mm D)	8,778	120/240 VAC, 104W
LUN2-60.00-L7SHD-NB-30K	60" DIA x 1.75" D (1,524mm DIA x 44mm D)	11,384	120/240 VAC, 134W

*Base model number shown only. To specify additional options, contact Electric Mirror at sales@electricmirror.com.

DIMENSIONAL DRAWING (Not to scale.)

