



VANITIES
BY ELECTRIC MIRROR®



EM

ASHBY™

Dimensions: 36"W x 24"D x 34"H

Materials:

- Wood Finish: Storm Cloud (SW6249), 60% sheen
- Countertop: Arctic Pearl (QT-1001), Polished
- Metal Finish: Chrome (CH-01), Polished

Metal Finish




Polished Chrome

Wood Finish



Storm Cloud

Countertop



Arctic Pearl

EM Mirror: [Momentum™ Lighted Mirror](#)



Features & Benefits

- 2 cm polished quartz countertop in Arctic Pearl (QT-1001).
- Quartz surfaces are highly resilient, nonporous, and scratch-and stain-resistant.
- Includes a rectangular undermount vitreous China sink.
- Stainless steel base finished in Polished Chrome (CH-01).
- Crafted with 5/8" MDF.
- Painted finish in Storm Cloud (SW6249) with a 60% sheen, achieved through a multistep finishing process.
- Features a 5-sided U-shaped dovetail drawer box, thoughtfully designed to allow space for plumbing while ensuring exceptional strength and durability.
- Equipped with premium undermount soft-close drawer slides for smooth, quiet operation.
- Freestanding design with cleat attachment for added security and stability.

Manufacturing & Quality Requirements

- All items must be of contract-grade quality, suitable for high-end hospitality use.
- Products must comply with local, state, national, and international codes, including ADA guidelines and fire/life safety regulations.
- Manufacturer must submit certificates of compliance, installation guidelines, maintenance instructions, and warranty documentation.
- All wood must be kiln-dried hardwood, marine-grade plywood, or waterproof MDF.
- Veneers must be A/B grade, with consistent grain and finish.
- All exposed edges must be sealed for moisture resistance.
- Finishes must be commercial-grade catalyzed lacquer, resistant to water, alcohol, and chemical stains.
- Vanities must be impact- and scratch-resistant, with matching finish on all sides and interiors.
- Drawer boxes must feature five-sided dovetail construction. Where plumbing interference exists, a U-shaped configuration should be used to maintain functionality without compromising structural integrity.
- All work must be corner blocked, glued, and reinforced with screws or appropriate mechanical fasteners.
- Use premium undermount soft-close slides and concealed soft-close hinges.
- All metal components and hardware must be made from 304 stainless steel, offering rust and corrosion resistance suitable for most environments. For coastal or high-humidity locations, 316 stainless steel must be used to ensure enhanced durability and protection against salt exposure.
- All exposed hardware finishes must be approved prior to production.
- Leveling glides must be heavy-duty, non-rust nylon, sized and colored to match the base or leg finish.
- Units must be properly packaged to prevent damage or soiling during transit.
- Shipping boxes must be labeled with property name, item number, PO number, and spec number.
- All products must be designed to fit within service elevators, corridors, and doorways. If not, items must be shipped in knock-down state for on-site assembly.
- Manufacturers must submit scaled shop drawings with full details (plans, elevations, sections, materials, finishes, hardware, dimensions).
- Finish samples must be submitted on appropriate substrates for approval prior to production.
- Review time for submittals is 5 business days.
- All substitutions or changes must be approved in writing by the designer.
- Coordinate with general contractor to confirm elevator cab sizes, corridor widths, and mounting heights.
- Manufacturers must ensure products are structurally sound, properly weighted to prevent tipping, and bolted where required (e.g., earthquake zones).

TECHNICAL DRAWINGS

VANITIES

BY ELECTRIC MIRROR®

CH-01: 304 STAINLESS STEEL BASE FINISHED IN POLISHED CHROME
 SW-6249: PAINTED FINISH IN STORM CLOUD WITH A 60% SHEEN
 QT-1001: 2 cm POLISHED QUARTZ COUNTERTOP IN ARCTIC PEARL
 SINK: INCLUDES A RECTANGULAR UNDERMOUNT VITREOUS CHINA SINK
 FAUCET: 3-PIECE FAUCET

