

# SOLIS™ LIGHTED PUBLIC SPACE MIRROR

## COMMERCIAL PRODUCT SPECIFIER



S     T     L     O     V     C

SOL4 -  -  -  - R180 - WR -  -

MODEL CODE     SIZE     TECHNOLOGY OPTIONS     LED TYPE     ORIENTATION     VOLTAGE     COLOR TEMP

ADDITIONAL NOTES <sup>1</sup>

### **S** MIRROR SIZE


In box S, enter the code for the size of the mirror.

Size (WxH)	Code
<b>Standard Mirror Sizes</b>	
60" x 72"	<b>60.00X72.00</b>
Custom <sup>2</sup>	WWWWXHH.HH

### **O** ORIENTATION

In box O, enter the code for the mirror orientation.

Mirror Orientation	Code
Flat Edge on Right or Left Side	<b>R180</b>



### **T** TECHNOLOGY OPTIONS

In box T, enter the codes for each option with a hyphen between each one.

Technology Options	Code
<b>Ava™ Touch-Tunable White Control on Mirror</b> <sup>2, 3, 4, 5</sup>	
▪ 1-Touch, 5 CCT Modes + Dimming	AH
▪ 1-Touch, 5 CCT Modes + Dim-to-Off + Memory	AK
<b>Wiring (Hardwire Standard—No Code Needed)</b>	
▪ 135° Offset Grounded Cord+Right-Angle Plug <sup>5</sup>	CC2
<b>Seamless™ LED Clock Technology</b> <sup>2, 3</sup>	
▪ Hardwired Clock, Switched with Lights	CK2
<b>Dimming Technology</b> <sup>4, 5</sup>	
▪ 0-10V Dimming (120-277VAC)	D1
▪ Forward-Phase/Triac Dimming (120-277VAC)	D2
▪ Dali Dimming (120-277VAC)	D4
<b>Defogger</b> <sup>5</sup>	
▪ Standard Defogger Pad	DF
<b>Keen™ One-Touch Energy-Saving Technology</b> <sup>2, 3, 4</sup>	
▪ 1-Touch, 5-Step Dimming, Off	KC

Indicates Standard Configuration

<sup>1</sup> Use the additional notes field to specify options not listed.

<sup>2</sup> Minimum order quantity required.

<sup>3</sup> See technology specification sheets for more details.

<sup>4</sup> Ava™ and Keen™ are not compatible with other dimming options.

<sup>5</sup> May not be compatible with all upgrades and options.

### **L** LED TYPE

In box L, enter the code for the LED type.

LED Type	Code
<b>Standard Output</b> <small>(853 lumens/ft; 6.72 watts/ft)</small>	<b>LSERD</b>
<b>High Output</b> <sup>5</sup> <small>(1,280 lumens/ft; 9.72 watts/ft)</small>	LHERD

### **V** VOLTAGE

In box V, enter the code for the voltage (code N/A for 120VAC).

Voltage	Code
<b>120VAC (Standard—Leave Code Blank)</b>	
220—240VAC	230V
277VAC <sup>5</sup>	277V

### **C** COLOR TEMPERATURE

In box C, enter the code for the correlated color temperature.

CCT (90+ CRI)	Code
2,700K (90+ CRI)	27K
<b>3,000K (90+ CRI)</b>	<b>30K</b>
3,500K (90+ CRI)	35K
4,000K (90+ CRI)	40K
5,000K (90+ CRI)	50K





## SOLIS™

### PRODUCT DESCRIPTION

Radiating quiet elegance, the Solis™ lighted public space mirror brings sculptural serenity and soft symmetry to public areas. Its gently rounded form is complemented by a subtle flat edge—an intentional design detail that allows it to nestle beautifully into a corner or align gracefully against a wall edge. This versatile geometry makes Solis both a functional fixture and a refined architectural element.

### SPECIFICATION STATEMENT

Solution shall consist of a mirror using 480-hour CASS-tested, lead-free, copper-free, corrosion-resistant glass with wall-glow accent lighting around the perimeter, providing uniform light to the walls at all edges of the mirror. The product shall use high-density (44 LEDs/foot), replaceable LED strips with 90+ CRI (Color Rendering Index) and delivering 853 initial lumens/foot with an efficacy of 140 lumens/watt. Product will be made in America with U.S and global components and have a 10-year limited warranty.

### THE ELECTRIC MIRROR ADVANTAGE

- ✓ Global mirror technology leader for over 25 years
- ✓ More installations than all competitors combined
- ✓ Realistic warranty you can believe in and trust
- ✓ Lowest total cost of ownership
- ✓ U.S.-based customer service support
- ✓ 125,000-square-foot American manufacturing facility

### LIGHTING FEATURES AND BENEFITS

- Industry-leading lumen output for better lighting
- Superior color rendering (CRI) for more natural, flattering, and softer light quality
- High-density linear LED design for even light distribution
- High-efficiency LEDs for best-in-class energy savings
- Perimeter wall-glow ambient lighting with diffuser for a finished side view

### GENERAL FEATURES AND BENEFITS

- OmegaMirror™ corrosion-resistant, 480-hour CASS-tested proprietary mirror glass
- Environmentally-leading, lead-free, copper-free mirror glass composition
- Fast lead times
- Easy installation
- ADA compliant
- JA8-2022 compliant
- 10-year limited warranty
- Patent: [www.electricmirror.com/patents](http://www.electricmirror.com/patents)
- Made in America with U.S. and global components

### AVAILABLE OPTIONS

- Title 24 compliance <sup>1</sup>
- [Ava™ touch-tunable white + dimming technology](#) <sup>2,3</sup>
- [Keen™ one-touch energy-saving dimming technology](#) <sup>2,3</sup>
- [Polaris™ wire-free motion sensor nightlight technology](#) <sup>2,3</sup>
- [Seamless™ LED clock technology](#) <sup>2,3</sup>
- [Vive™ streaming audio technology](#) <sup>2,3</sup>
- Defogger <sup>4</sup>
- CCT: 2,700K / 3,000K / 3,500K / 4,000K / 5,000K <sup>2</sup>
- 0-10V, phase/triac, or Dali dimming <sup>2,4</sup>
- 120VAC, 220–240VAC, or 277VAC power <sup>2,4</sup>
- Mirror orientation—flat edge on right or left side
- Custom sizes <sup>2</sup>

### DEFAULT LIGHTING SPECIFICATIONS

- Best-in-class illumination: 853 initial lumens/foot
- Superior color rendering: 90+ CRI
- High-density design: 44 LEDs/foot
- High efficacy: 140 lumens/watt
- Color temperature (CCT): 3,000K
- LED L<sub>70</sub> Lifespan (calculated): 52,000-hours
- Extended longevity: replaceable LEDs


<sup>1</sup> Title 24 compliance requires 0-10V or forward-phase/triac dimming.

<sup>2</sup> Minimum order quantity required.

<sup>3</sup> See technology specification sheets for more details.

<sup>4</sup> May not be compatible with all upgrades and options.

**DIMENSIONAL DRAWING** (Not to scale.)



**STANDARD MODELS**

Model Number <sup>1,4</sup>	Orientation	Dimensions <sup>2</sup>	Initial Lumens/ Fixture <sup>3</sup>	LED Power Requirements <sup>3</sup>
SOL4-60.00X72.00-LSERD-R180-30K	Flat edge on right or left side	60" W x 72" H x 1.63" D (1,524mm W x 1,829mm H x 41mm D)	14,620	120 or 277VAC, 116W

**SAFETY & INSTALLATION SPECIFICATIONS (for Standard Models)**

- Entire assembly meets UL/cUL standards
- International certifications
- Safety-backed mirror
- 120 or 277VAC hardwire electrical connection; direct wire from behind power box or provide whip to reach side knockout; junction box not required
- Fixture should be mounted to wall studs; wall cleat provided
- Controlled by non-dimming on/off wall switch (by others)
- Installation wiring may be different on mirrors equipped with additional options
- Fixture can be hung in the WxH orientation as shown with the flat edge on either the right or left side

<sup>1</sup> Standard model numbers shown. For assistance specifying additional options, please contact Electric Mirror.

<sup>2</sup> Tolerances for dimensions are  $\pm 1/8"$  ( $\pm 3\text{mm}$ ).

<sup>3</sup> Lumen output and power requirements are calculated based on component specifications and may vary from actual.

<sup>4</sup> Specifications and dimensions are subject to change without notice. Electric Mirror reserves the right to change the part number specified based on the latest standards.